

Product Overview

Excel solid Cat6 ethernet cable F/UTP LSOH CPR Euroclass Dca manufactured and tested to the TIA/EIA 568-B.2-1, EN50173-1 and ISO/ IEC 11801 Cat 6 specifications, 305m or 500m. Each cable consists of 8 colour coded solid copper conductors twisted together to form four pairs.

These are then formed around a central X-shaped polyethylene centre with the whole cable produced in a LSOH sheath.

Product Specifications

| Feature | Values |
|-------------------------------|--------------------|
| Conductor surface | Bare |
| AWG size | 23 |
| Conductor category | Class $1 = $ solid |
| Total number of cores | 8 |
| Stranding element | Pairs |
| Specification core insulation | PE |
| Core identification | Colour |
| Overall screening | Foil |
| Conductor screening | None |
| Outer sheath material | Copolymer |


Excel Solid Cat6 Cable F/UTP LSOH CPR Euroclass Dca 305m Reel Violet

Item Code: 100-076



| Outer sheath colour | Violet |
|---|--|
| Reaction-to-fire class according to EN 13501-6 | Dca |
| Smoke development class according to EN 13501-6 | s2 |
| Euro class flaming droplets/particles according to EN 13501-6 | d2 |
| Euro class acidity according to EN 13501-6 | al |
| Halogen free (acc. EN 60754-1/2) | Yes |
| Flame retardant | In accordance with EN 60332-1-2 and EN 50399 |
| | |
| Low smoke (acc. BS EN 61034-2) | Yes |
| Outer diameter approx. | Yes 7.2 mm |
| | |
| Outer diameter approx. | 7.2 mm |
| Outer diameter approx. Installation Temperature Range | 7.2 mm 050 °C |

Cross-section diagram



Cable specifications

| Features | Values |
|-------------------------|--------------|
| Dielectric strength | 2.5kV for 2s |
| Maximum pulling load | 60N/6.1KgF |
| MBR during installation | 8x cable OD |
| MBR installed | 4x cable OD |



Standards

| Applicable standard | Subject |
|-------------------------------|---|
| ISO/IEC 11801-1:2017 | Information technology - Generic cabling for customer premises: Part 1 General Requirements |
| IEC 61156-5:2020 | Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification |
| EN 50173-1:2018 | Information technology. Generic cabling systems - General requirements |
| EN 50173-2:2018 | Information technology. Generic cabling systems - Office premises |
| BS EN 50288-3-1:2013 | Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz |
| EN 50399:2011+A1:2016 | Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results |
| IEC 60332-1-2:2004 + A12:2020 | Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame |
| ANSI/TIA 568-D:2015 | Balanced Twisted-Pair Telecommunications Cabling and Components Standards |
| IEC 60754-2:2014 | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity |
| IEC 61034-2:2005+A2:2020 | Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements |
| EN 50575:2014 + A1:2016 | Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements |
| RoHS | Compliant to the Restriction of Hazardous Substances |
| WFD | Compliant to Waste Framework Directive |
| SCIP | Compliant - Does Not Contain Substances of Concern in Products |



Part Number Table

| Part Number | Description |
|------------------|---|
| 100-076 | Excel Solid Cat6 Cable F/UTP LSOH CPR Euroclass Dca 305m Reel Violet |
| 100-076/LTGN-500 | Excel Solid Cat6 Cable F/UTP LSOH CPR Euroclass Dca 500m Reel Light Green |
| 100-076-1000 | Excel Solid Cat6 Cable F/UTP LSOH CPR Euroclass Dca 1000m Reel Violet |
| 100-077/LTGN | Excel Solid Cat6 Dual Cable F/UTP LSOH CPR Euroclass Dca 500m Reel Light Green |
| 190-076 | Excel Solid Cat6 Cable F/UTP LSOH CPR Euroclass B2ca 305m Reel Violet |
| 190-076-305M-GN | Excel Category 6 Cable F/UTP B2ca LS0H 305m Easyreel Box - Green |
| 190-076-500 | Excel Solid Cat6 Cable F/UTP LSOH CPR Euroclass B2ca 500m Reel Violet |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.